




TERMINAL SCREWS ARE COMBINATION
10-32 PHIL-SLOT-1/4" HEX WITH SEMS WASHER



Transformer Specifications	
PRIMARY VOLTAGE(S)	240/347/380
SECONDARY VOLTAGE(S)	120X240
RATED V.A.	1500
RATED FREQUENCY	50/60
INSULATION CLASS	180
AGENCY APPROVALS	UL, CSA
ESTIMATED WEIGHT	50.6 LBS

TEST REQUIREMENTS			
WINDING	H4-H3-H2-H1	X4-X3	X2-X1
D.C. VOLTS	240.3-347.6-380	126.1	126.1
LOAD VOLTS	240-347-380	120	120
F.L. AMPS	7.060/4.459	6.250	6.250
HI-POT	4800V	3000V	
EXCITING AMPS	0.65AMPS MAX @ 380V, 50HZ		
EXCITING WATTS	50.2 MAX		



NOTE:
1. ALL MEASUREMENTS IN INCHES (MM)

PACKAGED ACCESSORIES	
1	1 PAIR OF J2 JUMPERS
-	-
-	-

800 664-4660
www.MicronTransformers.com

UL LISTED 702X

33135 CAT. NO. **B1K5-0322-3H**

ImperviTRAN
U.S. PAT. NO. 3516040

1.5 KVA 50/60 HZ
TEMP CL 180 °C

CONNECTION DIAGRAM CORRECTED	JAW	04/06/17
CUSTOMER REQUEST UPDATE PART LABEL	PJA	08/23/13
FORMAT REVISED	RN	09/16/08
REVISIONS	BY	DATE

MICRON INDUSTRIES CORPORATION
1211 W. 22nd STREET, Suite 200, OAK BROOK, ILL.
Tel. (800)664-4660, (630)516-1222 Fax (630)516-1820
www.MicronPower.com

DATE 09/16/08	DRAWN RN	CHECKED	APPROVED
RELEASE DATE	CUSTOMER PART NO.		
FINAL ASSY.		B1K5-0322-3HA0 B1K5-0322-3HB0	
SIZE C	SCALE NONE	B1K5-0322-3H	